

Ocean Container Specification Chart

	Inside Length	Inside Width	Inside Height	Door Width	Door Height	Cubic Capacity	Tare Weight	Max. Payload**
20' Standard	19'4"	7'8"	7'10"	7'8"	7'6"	1,172 cft	4,917 lbs	47,900 lbs
	5.89m	2.35m	2.39m	2.34m	2.28m	33.2 cbm	2,230kgs	21,770 kgs
40' Standard	39'5"	7'8"	7'10"	7'8"	7'6"	2,390 cft	8,160 lbs	59,040 lbs
	12.03m	2.35m	2.39m	2.34m	2.28m	67.7 cbm	3,700 kgs	26,780 kgs
40' High Cube	39'5"	7'8"	8'10"	7'8"	8'5"	2,694 cft	8,750 lbs	58,340 lbs
	12.03m	2.35m	2.69m	2.34m	2.58m	76.3 cbm	3,970 kgs	26,460 kgs
20' Open Top	19'4"	7'7"	7'8"	7'6"	7'2"	1,136 cft	5,280 lbs	47,620 lbs
	5.89m	2.31m	2.34m	2.28m	2.18m	32.2 cbm	2,395 kgs	21,600 kgs
40' Open Top	39'5"	7'8"	7'8"	7'8"	7'5"	2,350 cft	8,490 lbs	58,710 lbs
	12.03m	2.35m	2.34m	2.34m	2.26m	67.7 cbm	3,850 kgs	26,630 kgs
20' Reefer	17'8"	7'5"	7'5"	7'5"	7'3"	1,000 cft	7,040 lbs	45,760 lbs
	5.42m	2.26m	2.26m	2.26m	2.21m	28.3 cbm	3,193 kgs	20,757 kgs
40' Reefer	37'8"	7'5"	7'2"	7'5"	7'0"	2,040 cft	10,780 lbs	56,276 lbs
	11.49m	2.26m	2.18m	2.26m	2.13m	57.76 cbm	4,893 kgs	25,526 kgs
40' HC Reefer	37'11"	7'6"	8'2"	7'6"	8'0"	2,344 cft	9,900 lbs	57,561 lbs
	11.56m	2.29m	2.49m	2.29m	2.44m	66.37 cbm	4,491 kgs	26,109 kgs
20' Flat Rack	18'5"	7'3"	7'4"	-	-	-	5,578 lbs	45,760 lbs
	5.61m	2.21m	2.23m	-	-	-	2,530 kgs	20,757 kgs
40' Flat Rack	39'7"	6'10"	6'5"	-	-	-	12,081 lbs	85,800 lbs
	12.06m	2.08m	1.96m	-	-	-	5,480 kgs	38,918 kgs

All specifications are average measurements only

This information is provided as a guide to help you in determining the type of shipping container best suited to your needs. It is important to notice that some of these specs will vary from container to container, depending on the type of construction, manufacturer. *Please note that the cubic capacity of these containers is shown as an absolute maximum. The shipping packages are mostly in different sizes and shapes; hence the actual capacity can be substantially below these figures.

****Maximum weight allowance on individual units and shipments may vary. U.S. Department of Transportation (DOT) restricts maximum payload substantially lower than the payload shown above. Please contact World Cargo Solutions' representative to check specific equipment payload.**

